Member of the Feddersen Group – Germany

Website:www.imundex.vn
Email :support@imundex.vn

Member of the Feddersen Group – Germany

Three-Sided Stainless Steel Basket

Installation and Operation Instruction

Thank you for using IMUNDEX Products

Please read the following requirements before installation
1. The cabinet must be the standard cabinet matched to the sink (for L1).
2. The thickness of the side panels on both sides of the cabinet must be 16 or 18mm.
3. The cabinet must be installed horizontally and the ground must be flat and level.
4. This manual is suitable for the installation of the ordinary handle discs, special disc please refer to the general disc size and then adjust their own, or consult ERCEL technical department.
Note: If the cabinet failed to meet the requirements of point 1 or point 2, please do not install this product, thank you.

Daily maintenance and maintenance of products

1. Keep the inside of the basket clean and regularly cleaning the water tray.
2. To avoid the liquid spilled into the roll to ensure the normal work and life of the guide
3. Avoid contact with acid and alkaline, soy sauce, salt etc. in the basket

Common faults and handling methods

No.	Common Problem	Cause Analysis	Solution
1	Unsmooth Pulling Or Damping Failure	Roll damper is disabled / Roll damper damaged / Roll lubricant is dry / Deformation of rolls	Replace the roll damper / Replace the roll damper / Add lubricant / Replace the rolls
2	Door Cannot Shut Properly Or Door Can't Open	Roll damper is disabled / Pull basket installation error / Door assembly is not installed correctly	Replace the roll damper / Adjust the basket position / Adjust the door assembly position
3	Door Cannot Shut Properly Or Door Can't Open	Roll is not installed correctly / Door assembly is not installed correctly / Base deformation / Door deformation / Roll damper is disabled / Load overweight / Basket drive screw is loose	Adjust the roll mounting position / Adjust the door assembly position / Replace the base / Replace the door plate / Replace the roll damper / Adjust the protrusion in the basket / Tighten the screws
3	Appear Spot or Fuzz	Left uncleaned for long time / Material of basket	Clean the basket and water tray regularly
4	Hanging rail with pull basket pull and roll it not smooth	Roll damper is damaged / Basket weight exceeded	Use the force bottom / Reposition your items in the basket
5	Noise occurs when you pull or close the basket	Wrong connection lower rollers and lower wheel after long period of use	Properly fasten the connections / Add lubricating oil to each connecting part

Three Side Basket Parts Name



Three Side Basket Packing List

Bowl Shelf 1 piece	Back Panel 1 piece	Left & Right Side Panel 1 set	Left & Right Roll 1 set
Chopsticks Box 1 piece	Water Tray 1 piece	Trademark Cover 2 pieces	Door Installation Template 1 piece
Countersunk Head ST4*16 8 pieces	Round Head ST4*16 7 pieces	Expanded Screw 7 pieces	

Three Side Basket Parts Name



Three Side Basket Packing List

Flat Grid 1 piece	Back Panel 1 piece	Left & Right Side Panel 1 set	Left & Right Roll 1 set
Water Tray 1 piece	Trademark Cover 2 pieces	Door Installation Template 1 piece	Expanded Screw 7 pieces
Countersunk Head ST4*16 8 pieces	Round Head ST4*16 7 pieces		

Installation Step 1:
7.0. Refer to (Installation Step 2, 3, 4, 5, 6 Installation method), to install the upper basket;

Installation Step 8:
8.0. After adjusting the door, tighten all the screws, and then refer to the following figure to install the trademark cover on the top of the trademark cover.
8.1. This installation is complete



Installation Step 5:
5.0. Installing according to the direction of rotation, pop (before the connector)
5. Lock (Front connector), slant the front connector to loosen the screw.
b. Loosen the cross screws, turn clockwise, pop (front connector)
c. Tighten the screw, turn the screw, the front connector will be locked.
d. Loosen the cross screws, then turn the door left and right 6-2mm.



Installation Step 6:
6.0. In the direction of the arrow, place the (front connector) into the aluminum plate adjustment connector components, and then refer to (Installation step four) method to adjust the door.

Installation Step 7:
7.0. Installing the upper rails, first put the lower door into the cabinet, press the side panel and then put the roll on the door (see Figure A)
7.1. Put the upper door into the cabinet and adjust it.
7.1. After installing the upper rail, insert the lower rail to the bottom plate, then refer to (Figure B) to install the mounting rail screws.
7.2. Adjust the position of the door, and then tighten the bolt on the right
Note: The installation method for the rails for conventional handle door installation, special handle door is not suitable for use, please adjust the size of the installation or consult ERCEL hotline



Installation Step 2:
2.0. Pre-drill 2.5mm positioning holes by size or paper template size

Cabinet	600	700	800	900
L	535	635	735	835
L1	598	698	798	898



Installation Step 3:
3.0. On both sides of the basket, adjust the aluminum side panels according to the direction of the arrow and then tighten the screws as shown below:



Installation Step 4:
4.0. Place the main frame according to the arrow for correct positioning as shown in Figure A/B